

Cat. No. : 448

Description : Gas cartridge

Type :

Professional, for use with :

- Hot air gun Cat. No. 4600
- Roofer hoseless soldering iron Cat. No. 364
- Dehorner Cat. No. 144

Applications :

Sheet metal roofing, heat-shrinking tubes and sleeves, farming

Includes the following :

Foam cartridge:

Can be pointed downwards as soon as it is turned on

- Butane + 26% BIOPROPANE mixture
- Net gas mass : 60 g / 110 ml
- 18-bar steel casing (recyclable)

European standard screw valve :

- 7/16" – 28 threads per inch (60 °C – 140 °F)

Use in all seasons :

- Down to -13 °C (8.6 °F) with a new cartridge

Unit weight and dimensions :

- Weight: 120 g
- Diameter: 50 mm
- Height: 180 mm

Box weight and dimensions :

Box of 12 cartridges

- Weight: 1,5 kg
- Width: 180 mm
- Depth: 140 mm
- Height: 155 mm

Recommendations :

- Single-use, non-rechargeable cartridge.
- Keep away from sunlight
- Do not expose to temperatures exceeding 50 °C (122 °F)
- Store in a dry, well-ventilated room

Picture :



Safety Data Sheet (SDS) :

SDS N° 061

Compliance :

NF EN 417

Barcode

3 18964000448 1

IMPORTANT: Read instructions before use

GUILBERT EXPRESS reserves the right to change products without prior notice. Actual products may differ from photographs.

www.guilbert-express.net

GUILBERT EXPRESS

10 rue Henry Delbast - 77183 Croissy-Beaubourg - Tel: 0.825.800.251 - Fax: 0.825.800.238